

Central Joint Fire District

Standard Operating Procedure



Central Joint Fire District

SUBJECT: Vehicle Fire Response

SOP Number: 411B
Effective Date: 3/3/02
Revised Date:
Approved:

PURPOSE: The purpose of this standard is to define the proper response of equipment and apparatus to fires involved vehicles.

SCOPE: This standard shall apply to all Command Officers, Senior Firefighters or other persons who may find themselves responsible for the proper response of equipment and apparatus to fires involved vehicles.

ENFORCEMENT: The Officer in Charge shall be responsible for the enforcement of this standard and any deviations from this standard.

DEFINITION:

IC – Incident Commander

APPLICATIONS:

411B.1

A) The order of response shall be:

- 1) Engine 783 with at least two (2) members
- 2) Tanker 785 with at least two (2) members
- 3) Rescue 782 with at least two (2) members at IC discretion

B) Assignment:

- 1) Engine 783 with at least two (2) members shall proceed to the fire scene and commence fire scene operations.
- 2) Tanker 785 with two (2) members shall provide backup pumping capability and water supply as directed by the IC. Otherwise, the 785 crew shall fill out the crews operating at the fire scene as directed by the IC.
- 3) Rescue 782 with at least two (2) members shall proceed to fire scene to fill out the crews operating at the fire scene as directed by the IC.

411B.2 Response directly to the fire scene

- A) Only members who have direct radio communications with responding apparatus and appropriate personal protective equipment shall be permitted to respond directly to the fire scene per the IC.